

Geo-Fix™

Paving Joint Mortar

creating**better**living



Paving Joint Mortar, ready to use, air-cured joint mortar for natural stone, precast concrete paving and retaining walls, stone sets and cobbles.



Paved areas have never looked this good. Simply open the bag, pour the contents onto the paving and sweep into the joints. It's as easy as that. Geo-Fix™ is an air-curing joint filler for pavers and retaining wall faces.

Features and benefits:

- Permanent sand coloured joint unaffected by wind, rain and mechanical cleaning equipment.
- Non-staining.
- 20 times faster than traditional methods with easy broom no mess cleanup.
- Durable.
- Resists weed and plant growth between joints.
- Water and air permeable.
- Sold in more than 18 countries worldwide.

Preparation

Ensure that the paving to be jointed is completely dry and free from loose dirt, debris, oil and grease.

It is essential that joint widths have a minimum width of 5mm and a minimum depth of 25mm.

A trial area should always be undertaken.

Mixing

Boral Paving Joint Mortar is supplied ready to use and does not require any further mixing or dilution. Because of the vacuum used to store the product, bags should be hard to touch, but the material inside should be soft and lump free.

Curing & storage

Curing takes 2-12 hours depending on temperature.

Store in a cool dry place. Protect the pack, both outer and inner, from punctures or piercing. Exposure to air will start the curing process.

Shelf life is a minimum of 24 months when stored in unopened vacuum sealed packaging.

Application



STEP 1
Carefully open the vacuum-packed bag and sprinkle Boral Paving Joint Mortar over the area to be jointed.




STEP 2
Using a soft brush, push the Boral Paving Joint Mortar into the joints at a 45° angle.




STEP 3
Firmly compact the Boral Paving Joint Mortar with a jointing tool. Refill and repeat ensuring a fully compacted and topped joint.



STEP 4
Finish the surface decoratively giving a smooth, flat finish with a jointing tool then move onto the next area. Firm compaction is the key to successful laying of Boral Paving Joint Mortar.



STEP 5
After application brush off excess with a soft brush, taking care not to brush out any Boral Paving Joint Mortar from treated joints. Once cured, sit back and enjoy your new patio.



Coverage

Coverage Joint Width	Paving Dimension (with joint depth of 25mm)		
	250x250mm	450x450mm	600x600mm
5mm	6.50m ²	11.00m ²	13.25m ²
6mm	5.50m ²	9.50m ²	11.00m ²
7mm	4.50m ²	8.25m ²	8.75m ²
8mm	3.90m ²	7.25m ²	8.25m ²
9mm	3.25m ²	6.00m ²	7.25m ²
10mm	2.90m ²	5.50m ²	6.50m ²

Orders and sales enquiries

NSW
Boral Masonry
Clunies Ross St
Prospect NSW 2148
Tel (02) 9840 2333
Fax (02) 9840 2344

VIC
Boral Masonry
Riding Boundary Rd
Deer Park VIC 3023
Tel (03) 9363 1944
Fax (03) 9363 6008

SA
Boral Masonry
Main North Rd
Pooraka SA 5095
Tel (08) 8262 3529
Fax (08) 8260 3077

STH QLD
Boral Masonry
62 Industrial Ave
Wacol QLD 4076
Tel (07) 3721 9292
Fax (07) 3721 1581

NTH QLD
David Muir St
Slade Point 4740
Tel (07) 4955 1155
Fax (07) 4955 4130
360 Bayswater Rd
Garbutt 4814
Tel (07) 4725 6011
Fax (07) 4725 6043

NTH QLD
8 Palmer St
Portsmith QLD 4870
Tel (07) 4035 1888
Fax (07) 4035 1208

For technical assistance:

Call **Boral Ideas Line on 1300 134 002**

Visit **www.boral.com.au/geofix**

Front Cover: Geo-Fix™ and River Pebble™ pavers.
We reserve the right to change the details in this publication without notice. For a full set of Terms and Conditions of Sale please contact your nearest Boral Masonry sales office.
Geo-Fix™ and River Pebble™ is a registered trademark of Boral Masonry Limited. © Boral Masonry. All Rights Reserved 2007.
Boral Masonry Limited ABN 13 000 223 718.